


VOSSEN

Carpet Tiles



ALPHA

Product	ALPHA
Construction	LOOP
Pile Fiber Composition	100% Olefin
Yarn Type	BCF
Dye Method	Solution Dyed
Pile Weight	550 g/m ²
Number of Tufts	248850/m ²
Tufting Gauge	1/10"
Primary Backing	Non-Woven
Secondary Backing	StableShield-100% Vinyl
Tile Size	50 cm x 50 cm / 1m x 1m (optional)
Total Tile Height	6.0 mm
Pile Treatment	INVISTA Anti-Soil Treatment

Performance Specifications

Wear Classification	Heavy Contract	
VOC Emission	ASTM D5116-06	<0.5 mg/m ² /hour [CRI GLP]
Flammability	ASTM D-2859//FF 1-70//16CFR 1630	Pass 8/8
Critical Radiant Flux	EN ISO 9239 - 1 - 2002	Dfl - s1
Static Propensity	ISO 6356	0.2 kV
Color Fastness	AATCC/16	5/5 on Grey Scale
Thermal Resistance	ISO 8302	.04m ² K/W
Impact Sound Insulation	ISO 140-8	ΔLw 23dB
Sound Absorption Level	EN ISO 11654	αw: 0.15(H)
Soiling Propensity	ASTM D 6540-00	4
Dimensional Stability	EN 986	< 0.20%
Castor Chair Test	DIN 54324	R ≥ 2.4
Smoke Density	EN ISO 9239-1:2002	<450

The above Information is subject to modification for the benefit of further improvement.

