



CARPET TILES

## SPECIFICATION SHEET

## CLICK

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| CONSTRUCTION             | LOOP                                              |
| FIBER COMPOSITION        | 100% Nylon (Polyamide6)                           |
| YARN TYPE                | CABLE                                             |
| DYE METHOD               | Solution Dyed                                     |
| PILE WEIGHT              | 560g/m <sup>2</sup>                               |
| NUMBER OF TUFTS          | 197000/m <sup>2</sup>                             |
| TUFTED GAUGE             | 1/10"                                             |
| PRIMARY BACKING          | Non-Woven                                         |
| SECONDARY BACKING        | StableShield 100% Vinyl                           |
| OPTIONAL BACKING         | Recova-Pu Cushion, Eco Shield 100% Recycled Vinyl |
| TILE SIZE                | 50x50cm                                           |
| PILE HEIGHT              | 3.0mm                                             |
| TOTAL HEIGHT             | 6.0mm                                             |
| PILE & BACKING TREATMENT | INVISTA Anti-Soil Treatment                       |
| RECOMMENDED              | Quarter Turn or Brick                             |

## PERFORMANCE SPECIFICATION

|                         |                                  |                                        |
|-------------------------|----------------------------------|----------------------------------------|
| WEAR CLASSICATION       | HEAVY CONTRACT                   |                                        |
| VOC EMISSION            | ASTM D5116-06                    | <0.5 mg/m <sup>2</sup> /hour (CRI GLP) |
| FLAMMABILITY            | ASTM D-2859//FF 1-70//16CFR 1630 | Pass 8/8                               |
| CRITICAL RADIANT FLUX   | ASTM E648-08                     | Class 1                                |
| STATIC PROPENSITY       | ISO 6356                         | 0.2 kV                                 |
| COLOR FASTNESS          | AATCC/16                         | 5/5 on Grey Scale                      |
| THERMAL RESISTANCE      | ISO 8302                         | .04m <sup>2</sup> K/W                  |
| IMPACT SOUND INSULATION | ISO 140-8                        | ΔLw 23dB                               |
| SOUND ABSORPTION LEVEL  | EN ISO 11654                     | αw: 0.15(H)                            |
| SOILING PROPENSITY      | ASTM D 6540-00                   | 4                                      |
| DIMENSIONAL STABILITY   | EN 986                           | < 0.20%                                |
| CASTOR CHAIR TEST       | DIN 54324                        | R ≥ 2.4                                |
| SMOKE DENSITY           | EN ISO 9239-1:2002               | <450                                   |



WEAR  
STABILITY  
CASTOR CHAIR  
COMPATIBILITY  
ANTISTATIC  
LIGHT FASTNESS

BREEAM®

Standard  
CARPETS

- Shading or Pile reversal is an inherent attribute of cut pile carpets and not a manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies

Standard Carpets Ind LLC  
P.O. Box No. 490014  
Dubai Industrial Park, Dubai UAE  
T: +971 4 554 7137 | F: +971 4 554 7132  
E: info@standardcarpets.com | www.standardcarpets.com

Standard Carpets Ind LLC  
P.O. Box No. 490014  
Dubai Industrial Park, Dubai UAE  
Made In The UAE. The largest manufacturer of tufted carpets and  
the only manufacturer of carpet tiles in the United Arab Emirates.

Standard Carpets are manufactured under the  
environmental quality system certified and complying  
with ISO 18001 by an accredited certification body.