



CARPET TILES

# SPECIFICATION SHEET

## ON THE ROCKS

| CONSTRUCTION             | SCROLL LOOP PILE            |
|--------------------------|-----------------------------|
| PILE FIBER COMPOSITION   | 100% Nylon                  |
| YARN TYPE                | Cable                       |
| DYE METHOD               | Solution Dyed               |
| PILE WEIGHT              | 700 g/m <sup>2</sup>        |
| NUMBER OF TUFTS          | 244280/m <sup>2</sup>       |
| TUFTING GAUGE            | 1/10"                       |
| PRIMARY BACKING          | Non-Woven                   |
| SECONDARY BACKING        | StableShield- 100% Vinyl    |
| TILE SIZE                | 50 cm x 100 cm              |
| PILE HEIGHT              | 3.50 mm (+/-5%)             |
| TOTAL HEIGHT             | 6.60 mm (+/-5%)             |
| PILE TREATMENT           | UV Treated Yarn             |
| RECOMMENDED INSTALLATION | Quarter Turn or Herringbone |

## PERFORMANCE SPECIFICATION

| WEAR CLASSIFICATION     | HEAVY CONTRACT                   |                                        |
|-------------------------|----------------------------------|----------------------------------------|
| VOC EMISSION            | ASTM D5116-06                    | <0.5 mg/m <sup>2</sup> /hour (CRI GLP) |
| FLAMMABILITY            | ASTM D-2859//FF 1-70//16CFR 1630 | Pass 8/8                               |
| CRITICAL RADIANT FLUX   | ASTM E648-08                     | Class 1                                |
| STATIC PROPENSITY       | ISO 6356                         | 0.2 kV                                 |
| COLOR FASTNESS          | AATCC/16                         | 5/5 on Grey Scale                      |
| THERMAL RESISTANCE      | ISO 8302                         | .04m2 K/W                              |
| IMPACT SOUND INSULATION | ISO 140-8                        | ΔLw 23dB                               |
| SOUND ABSORPTION LEVEL  | EN ISO 11654                     | αw: 0.15(H)                            |
| SOILING PROPENSITY      | ASTM D 6540-00                   | 4                                      |
| DIMENSIONAL STABILITY   | EN 986                           | < 0.20%                                |
| CASTOR CHAIR TEST       | DIN 54324                        | R ≥ 2.4                                |
| SMOKE DENSITY           | EN ISO 9239-1:2002               | <450                                   |



- Shading or Pile reversal is an inherent attribute of cut pile carpets and it is not manufacturing defect
- Color may slightly vary from one dye lot to another dye lot
- Total weight of the product can have a normal variation of ± 5%
- We reserve the right to amend the above specification without prior notice with changes in raw material supplies

Standard Carpets Ind LLC  
P.O. Box No. 490014  
Dubai Industrial Park, Dubai UAE  
T: +971 4 554 7137 | F: +971 4 554 7132  
E: info@standardcarpets.com | www.standardcarpets.com

Standard Carpets Ind LLC  
P.O. Box No. 490014  
Dubai Industrial Park, Dubai UAE  
Made In The UAE. The largest manufacturer of tufted carpets and the only manufacturer of carpet tiles in the United Arab Emirates.

Standard Carpets are manufactured under the environmental quality system certified and complying with ISO 18001 by an accredited certification body.

