

LVT FLOORING
CLICK
WEAR LAYER: 0.55 mm
THICKNESS: 5 mm
235 x 1505 (MM) - 185 x 1212 (MM)

Size & Packing

Size(mm)		Thickness(mm)	Pcs / BOX	m ² / BOX
185 x 1212		5	8	1.79
235 x 1505			6	2.12
304.8 x 609.6	12" x 24"		10	1.86
457.2 x 914.4	18" x 36"		6	2.56

Test Result

Test Item	Standard	Ecoclick ⁺
Level of use	EN 685	23 / 33 / 42
Dimensional stability	ISO 23999 / EN 434	≤0.10% (Norm±0.25%)
Abrasion group	EN 660-2	Class T
Castor chair resistance	EN 425	No damage
Squareness & Straightness	ISO 24342	≤ 400mm :≤0.25mm
		>400mm :≤0.35mm
	ASTM F2055	≤ 0.01 in
Residual Indentation	EN 433	≤ 0.1mm
	ASTM F1914	<8%
Impact sound insulation	ISO 10140-3	9dB
Light fastness	ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS
	DIN51130	R10
Resistance to chemicals	ISO 26987	No Defects
	ASTM F925	No Defects
Thermal resistance	ISO 8302	0.01m ² K/W
Curling after exposure to heat	ISO 23999	≤ 2mm
Fire resistance	EN 13501-1	Bfl -s1
Flexibility	ISO 24344	Passed
	ASTM F137	Passed
Body Voltage	EN 1815	<2kV
Resistance against staining	ISO 26987	Passed
Underfloor heating suitability	EN 12524	Suitable
Formaldehyde group	EN 717-1	E1
Indoor air quality		Low VOC

